



PARK SIGN

KEYED NOTES:

- ① PARK NAME BY SIGN MANUF.
- ② EXISTING GROUND TO REMAIN UNDISTURBED. DISTURBED GROUND TO BE COMPACTED TO 90% AS PER ASTM D1557.
- ③ FINISHED GRADE, SEE GRADING PLAN
- ④ CONTINUOUS CONCRETE FOOTING.
- ⑤ PRE-CAST CONCRETE SIGN BY WASAU TILE, REFER TO SPEC.
- ⑥ 3000 PSI CONCRETE BASE
- ⑦ 2" ROCK VENEER, MOUNT. FRANKLIN ROCK.
- ⑧ 4 # 4'S CONT. W/#4 @ 12" O.C.
- ⑨ 12" ENGINEERED FIELD COMPACTED TO MODIFIED PROCTOR TO 95%.
- ⑩ CONCRETE BASE BY SIGN MANUF.
- ⑪ S/S STUD ANCHOR PROVIDED BY SIGN MANUF.
- ⑫ 3" X 14" DEEP LEAVE-OUT FOR ANCHORING SIGN BY SIGN MANUF.
- ⑬ PROVIDE GROUT & CEMENT FOR LEVELING SIGN.

DETAIL NO.
502



CITY OF EL PASO  
PARKS & RECREATION

DETAIL NAME

PARK MONUMENT SIGN # 1  
NTS