



- A. PROVIDE DEWITT PRO 5 WEED CLOTH ALONG SIDES AND BASE OF VALVE BOX INSTALLATION. TAPE TO ALL INLET AND OUTLET PIPE AND VALVE BOX WITH HEAVY DUTY PLASTIC 3M TAPE.
- B. AIR RELEASE VALVE.
- C. CARSON PRODUCTS, INC. 1419-18 (ABS) VALVE BOX WITH BOLT DOWN COVER, EXTENSIONS AS NECESSARY. COLOR TO MATCH FINISHED MATERIAL.
- D. FINISH GRADE.
- E. 8"X8"X16" SOLID CMU BLOCK @ EACH CORNER.
- F. 1 CUBIC FOOT 3/8" WASHED PEA GRAVEL.
- G. LASCO-PREASSEMBLED SWING JOINT.
- H. IRRIGATION MAINLINE/LATERAL MAINLINE.
- I. 6" DEPTH OF 3/8" PEA GRAVEL.
- J. PVC TEE FITTING.

NOTE: PVC PIPE TO BE CLEAR OF VALVE BOX AND SOLID CMU BLOCK.

DETAIL NO.

300



CITY OF EL PASO
PARKS & RECREATION

DETAIL NAME

AIR RELEASE VALVE
NTS